

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.03.2018

Version number 3

Revision 20.03.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** *Interflon Grease HTG (aerosol)*
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** *Lubricant*
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Interflon b.v.
P.O. Box 1070
NL-4700 BB Roosendaal
The Netherlands
Tel: +31(0)165.55.39.11
Email: service@interflon.com
www.interflon.com
- **Further information obtainable from:** *Product safety department*
- **1.4 Emergency telephone number:** *UK National Poisons Emergency number: +44 870 600 6266*

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**

<i>Aerosol 1</i>	<i>H222-H229</i>	<i>Extremely flammable aerosol. Pressurised container: May burst if heated.</i>
<i>Skin Irrit. 2</i>	<i>H315</i>	<i>Causes skin irritation.</i>
<i>STOT SE 3</i>	<i>H336</i>	<i>May cause drowsiness or dizziness.</i>
<i>Asp. Tox. 1</i>	<i>H304</i>	<i>May be fatal if swallowed and enters airways.</i>
<i>Aquatic Chronic 3</i>	<i>H412</i>	<i>Harmful to aquatic life with long lasting effects.</i>

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02 GHS07

- **Signal word** *Danger*
- **Hazard-determining components of labelling:**
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics
Hydrocarbons, C6, isoalkanes, <5% n-hexane
n-hexane
- **Hazard statements**
H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.03.2018

Version number 3

Revision 20.03.2018

Trade name: Interflon Grease HTG (aerosol)

(Contd. of page 1)

· **Precautionary statements**

- P210 *Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.*
P211 *Do not spray on an open flame or other ignition source.*
P251 *Do not pierce or burn, even after use.*
P261 *Avoid breathing mist/vapours/spray.*
P280 *Wear protective gloves.*
P410+P412 *Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.*

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

- **PBT:** Material does not meet the criteria for PBT according to Regulation (EC) No 1907/2006, Annex XIII.
· **vPvB:** Material does not meet the criteria for vPvB according to Regulation (EC) No 1907/2006, Annex XIII.

SECTION 3: Composition/information on ingredients

· **3.2 Mixtures**

· **Description:**

Mixture of synthetic oils, inorganic thickener, solvent, additives and Teflon®. Propellant gas propane, butane and isobutane.

· **Dangerous components:**

CAS: 106-97-8 EINECS: 203-448-7	butane (Nota K, <0,1% 1,3-butadiene) Flam. Gas 1, H220; Press. Gas (Comp.), H280	10 – 25%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21	propane Flam. Gas 1, H220; Press. Gas (Comp.), H280	10 – 25%
CAS: 75-28-5 EINECS: 200-857-2	isobutane (Nota K, <0,1% 1,3-butadiene) Flam. Gas 1, H220; Press. Gas (Comp.), H280	10 – 25%
EC number: 927-510-4 Reg.nr.: 01-2119475515-33	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	10 – 25%
EC number: 927-241-2 Reg.nr.: 01-2119471843-32	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336; Aquatic Chronic 3, H412	2.5 – 10%
EC number: 931-254-9 Reg.nr.: 01-2119484651-34	Hydrocarbons, C6, isoalkanes, <5% n-hexane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	2.5 – 10%
CAS: 110-54-3 EINECS: 203-777-6	n-hexane Flam. Liq. 2, H225; Repr. 2, H361f; STOT RE 2, H373; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	0.25 – ≤ 2.5%
CAS: 110-82-7 EINECS: 203-806-2	cyclohexane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315; STOT SE 3, H336	0.1 – ≤ 0.25%

· **SVHC**

This product does not contain "very worrisome substances" (SVHC) that are very dangerous to human health or the environment. (SVHC <0.1% (w / w) Regulation (EC) No. 1907/2006 (REACH), Article 57).

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.03.2018

Version number 3

Revision 20.03.2018

Trade name: Interflon Grease HTG (aerosol)

(Contd. of page 2)

· Additional information:

Note: Any entry in the EC column that begins with the number "9" is a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance. See Section 16 for additional CAS number information for the substance.

See SDS Section 16 for full text of hazard statements.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information: Immediately remove any clothing soiled by the product.

· After inhalation:

Remove person to fresh air and keep comfortable for breathing.

In case of unconsciousness place patient stably in side position for transportation.

Call a POISON CENTER/doctor if you feel unwell.

· After skin contact:

Take off immediately all contaminated clothing.

Wash with plenty of soap and water.

If skin irritation occurs: Get medical advice/attention.

· After eye contact:

Rinse cautiously with water for several minutes.

If eye irritation persists: Get medical advice/attention.

· After swallowing: If symptoms persist consult doctor.

· 4.2 Most important symptoms and effects, both acute and delayed

Acute and delayed effects are indicated in sections 2 and 11.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media**· Suitable extinguishing agents:**

Use fire extinguishing methods suitable to surrounding conditions

CO₂, sand, powder, water spray.

Foam

· 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

Carbon monoxide (CO)

Hydrogen fluoride and other fluoride compounds.

· 5.3 Advice for firefighters**· Protective equipment:**

Wear self-contained respiratory protective device.

Use personal protective equipment (EN469).

· Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

GB

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.03.2018

Version number 3

Revision 20.03.2018

Trade name: Interflon Grease HTG (aerosol)

(Contd. of page 3)

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Particular danger of slipping on leaked/spilled product.
- **6.2 Environmental precautions:**
Do not allow to enter sewers/ surface or ground water.
Inform respective authorities in case of seepage into water course or sewage system.
- **6.3 Methods and material for containment and cleaning up:**
Clear spills immediately.
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Remove residues with alkaline cleaning agent.
- **6.4 Reference to other sections**
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Do not spray on an open flame or other ignition source.
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in accordance with local/regional/national/international regulations.
Observe official regulations on storing packagings with pressurised containers.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
Store in a well-ventilated place.
Keep container tightly closed.
Store in a dry place.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Store in a cool place.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**

Ingredients with limit values that require monitoring at the workplace:
106-97-8 butane (Nota K, <0,1% 1,3-butadiene)

WEL (Great Britain)	Short-term value: 1810 mg/m ³ , 750 ppm Long-term value: 1450 mg/m ³ , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
---------------------	---

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.03.2018

Version number 3

Revision 20.03.2018

Trade name: Interflon Grease HTG (aerosol)

(Contd. of page 4)

110-54-3 n-hexane

WEL (Great Britain) Long-term value: 72 mg/m³, 20 ppm

IOELV (EU) Long-term value: 72 mg/m³, 20 ppm

110-82-7 cyclohexane

WEL (Great Britain) Short-term value: 1050 mg/m³, 300 ppm

Long-term value: 350 mg/m³, 100 ppm

IOELV (EU) Long-term value: 700 mg/m³, 200 ppm

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Do not inhale gases / fumes / aerosols.

Immediately remove all soiled and contaminated clothing

Avoid contact with the eyes and skin.

Wash hands before breaks and at the end of work.

Do not eat, drink, smoke or sniff while working.

· **Respiratory protection:** Not required.

· **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Practical experience has shown that gloves of Nitril offer sufficient protection.

Glove thickness: 0,13 mm

Breakthrough time: > 15 minutes

· **Penetration time of glove material** The penetration times are not determined by method EN 374 Part 3.

· **Eye protection:** Not required.

· **Body protection:** Wear suitable protective clothing (EN ISO 13688).

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Aerosol

Colour: Brown

· **Odour:** Recognisable

· **Odour threshold:** Not determined.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.03.2018

Version number 3

Revision 20.03.2018

Trade name: Interflon Grease HTG (aerosol)

(Contd. of page 5)

· pH-value:	Not applicable.
· Change in condition Melting point/freezing point:	Not applicable.
Initial boiling point and boiling range:	< 0 °C
· Flash point:	< -60 °C
· Flammability (solid, gas):	Flammable.
· Ignition temperature:	Not determined.
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits: Lower:	1.5 Vol %
Upper:	10 Vol %
· Vapour pressure at 20 °C:	3800 hPa
· Density at 20 °C:	0.66 g/cm ³
· Relative density	Not determined.
· Vapour density at 20 °C	1.6 - 2.0 g/cm ³
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Viscosity: Dynamic:	Not determined.
Kinematic:	Not applicable.
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No reactivity hazards known under normal storage and use conditions.
- **10.2 Chemical stability** Stable under normal storage and use conditions.
- **Thermal decomposition / conditions to be avoided:** To avoid thermal decomposition do not overheat.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid**
Conditions to be avoided: sun-ray, temperatures above 50°C, open fire, piercing can.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- **10.5 Incompatible materials:** Strong oxidising agents.
- **10.6 Hazardous decomposition products:**
Carbon monoxide and partially combusted carbohydrates can be released during thermal decomposition.
Fluoride compounds can be released from 400 °C.

GB

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.03.2018

Version number 3

Revision 20.03.2018

Trade name: Interflon Grease HTG (aerosol)

(Contd. of page 6)

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

106-97-8 butane (Nota K, <0,1% 1,3-butadiene)

Inhalative	LC50/4 h	253599 ppm (Rat)
------------	----------	------------------

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics

Oral	LD50	> 5000 mg/kg (Rat) (OECD 401)
------	------	-------------------------------

Dermal	LD50	> 5000 mg/kg (Rabbit) (OECD 402)
--------	------	----------------------------------

110-54-3 n-hexane

Oral	LD50	25000 mg/kg (Rat)
------	------	-------------------

Inhalative	LC50/4 h	169 mg/l (Rat)
------------	----------	----------------

110-82-7 cyclohexane

Oral	LD50	12705 mg/kg (Rat)
------	------	-------------------

Primary irritant effect:

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Subacute to chronic toxicity: No further relevant information available.

STOT SE (Specific target organ toxicity – single exposure): May cause drowsiness or dizziness.

STOT RE (Specific target organ toxicity – repeated exposure): No further relevant information available.

Additional toxicological information:

The thermal decomposition vapours of fluorinated polymers may cause polymer fume fever, which has flu-like symptoms in humans, especially when smoking contaminated tobacco.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

This product does not fulfil the criteria for classification of CMR (carcinogen, mutagen, toxic to reproduction).

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard

Product is classified as presenting an aspiration hazard, but need not be labelled for this hazard according to point 1.3.3 of Annex I to Regulation (EC) No 1272/2008.

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

Harmful to aquatic life with long lasting effects.

110-54-3 n-hexane

LC50 96 hr	2.5 mg/l (Fish)
------------	-----------------

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.03.2018

Version number 3

Revision 20.03.2018

Trade name: Interflon Grease HTG (aerosol)

(Contd. of page 7)

· 12.2 Persistence and degradability

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics

Biodegradability 89 % (-)

· 12.3 Bioaccumulative potential No further relevant information available.

· 12.4 Mobility in soil No further relevant information available.

· Ecotoxicological effects:

· Remark: Harmful to fish

· Additional ecological information:

· General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

· 12.5 Results of PBT and vPvB assessment

· PBT: Material does not meet the criteria for PBT according to Regulation (EC) No 1907/2006, Annex XIII.

· vPvB: Material does not meet the criteria for vPvB according to Regulation (EC) No 1907/2006, Annex XIII.

· 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Waste should not be disposed of by release to sewers.

Final decisions on the appropriate waste management method, in line with regional, national and European legislation, and possible adaptation to local conditions, remains the responsibility of the waste treatment operator.

· European waste catalogue

20 01 26*	oil and fat other than those mentioned in 20 01 25
16 05 04*	gases in pressure containers (including halons) containing hazardous substances
15 01 04	metallic packaging
HP 3	Flammable
HP 14	Ecotoxic

· Uncleaned packaging:

· Recommendation:

Dispose of contents/container in accordance with local/regional/national/international regulations.

SECTION 14: Transport information

· 14.1 UN-Number

· ADR, IMDG, IATA

UN1950

· 14.2 UN proper shipping name

· ADR

1950 AEROSOLS

· IMDG

AEROSOLS

· IATA

AEROSOLS, flammable

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.03.2018

Version number 3

Revision 20.03.2018

Trade name: Interflon Grease HTG (aerosol)

(Contd. of page 8)

· 14.3 Transport hazard class(es)

· ADR



· **Class** 2 5F Gases.
· **Label** 2.1

· 14.4 Packing group

· **ADR, IMDG, IATA** Void

· **14.5 Environmental hazards:** Not applicable.

· 14.6 Special precautions for user

· **Danger code (Kemler):** Warning: Gases.

· **EMS Number:** -

· **Stowage Code** F-D,S-U

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

· **Segregation Code** SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

· **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.

· Transport/Additional information:

· ADR

· **Limited quantities (LQ)** 1L

· **Transport category** 2

· **Tunnel restriction code** D

· **UN "Model Regulation":** UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category P3a** FLAMMABLE AEROSOLS

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

· **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3, 57

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.03.2018

Version number 3

Revision 20.03.2018

Trade name: Interflon Grease HTG (aerosol)

(Contd. of page 9)

- **National regulations:**
- **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.
This safety datasheet only contains information relating to safety and does not replace any product information or product specification.

The following substance(s) in this product is (are) identified by the CAS number(s) shown in countries not subject to the REACH regulation.

Hydrocarbons, C6, isoalkanes, <5% n-hexane: CAS 64742-49-0

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics: CAS 92045-53-9

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics: CAS 64742-48-9

· Relevant phrases (code and full text as stated in chapter 3)

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3.

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H361f Suspected of damaging fertility.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

· Classification according to Regulation (EC) No 1272/2008

Aerosols	Bridging principles
Skin corrosion/irritation Specific target organ toxicity (single exposure) Hazardous to the aquatic environment - long-term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.
Aspiration hazard	Expert judgement

· Department issuing SDS: Product safety department.

· Contact:

Head Laboratory

Email: service@interflon.com

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

(Contd. on page 11)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.03.2018

Version number 3

Revision 20.03.2018

Trade name: Interflon Grease HTG (aerosol)

(Contd. of page 10)

EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 LC50: Lethal Concentration, 50 percent
 LD50: Lethal Dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 SVHC: Substances of Very High Concern
 vPvB: very Persistent and very Bioaccumulative
 REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals
 CLP: Classification, Labelling and Packaging of substances and mixtures
 ECHA: European Chemicals Agency
 EC50: Effective Concentration, 50 percent
 IC50: Inhibitory Concentration, 50 percent
 LL/EL/IL: Lethal Loading/Exposure Limit/Inhibition Limit
 LL50: Lethal Loading, 50 percent
 EL50: Effective Loading, 50 percent
 IL50: Inhibitory Level, 50 percent
 NOEC/NOEL: No Observed Effect Concentration / No Observed Effect Level
 OECD: Organisation for Economic Cooperation and Development
 Flam. Gas 1: Flammable gases – Category 1
 Aerosol 1: Aerosols – Category 1
 Press. Gas (Comp.): Gases under pressure – Compressed gas
 Flam. Liq. 2: Flammable liquids – Category 2
 Flam. Liq. 3: Flammable liquids – Category 3
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Repr. 2: Reproductive toxicity – Category 2
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
 Asp. Tox. 1: Aspiration hazard – Category 1
 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· **Key literature references and sources for data:**

- Regulation (EC) No. 1907/2006 (REACH), amended by 2015/830/EU
- Regulation (EC) No. 1272/2008 (CLP, EU GHS)
- ECHA database on registered substances
- EU IUCLID Database
- Material suppliers' data

· *** Data compared to the previous version altered.**