

## MINERAL GEAR OIL.

This is an extreme-pressure lubricant for gear boxes, specifically formulated to satisfy the highest service conditions: high speed, shockloads and high torque at low speeds.



## APPLICATIONS

Recommended for all hypoid transmissions and also suitable for spiral bevel gears, worm wheels and most transaxles.

## PERFORMANCE LEVEL

- API: GL-5
- MAN: 342 M-1
- MAN: 342 M-2
- MIL: MIL-L-2105 C
- MIL: MIL-L-2105 D
- ZF: TE-ML 05A
- MB 235.0
- ZF: TE-ML 07A
- ZF: TE-ML 12E
- ZF: TE-ML 12M
- ZF: TE-ML 12N
- ZF: TE-ML 16B
- ZF: TE-ML 16C
- ZF: TE-ML 17B
- ZF: TE-ML 19B

## FEATURES

Frictional properties : easy gear shifting.  
Anti-wear protection : long transmission life.

## CHARACTERISTICS

|                  | unit               | method | average value |
|------------------|--------------------|--------|---------------|
| Density at 15 °C | kg/l               |        | 0.893         |
| Viscosity 40 °C  | mm <sup>2</sup> /s |        | 150.50        |
| Viscosity 100 °C | mm <sup>2</sup> /s |        | 15.20         |
| Viscosity Index  |                    |        | 102           |
| Flash Point COC  | °C                 |        | 214           |
| Pour Point       | °C                 |        | -27           |

## PACKAGING

