



SAFETY DATA SHEET

Simoniz Underguard

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Simoniz Underguard

Product number SIMR14D

UFI UFI: JCA6-E05X-600Q-74XH

EU REACH registration notes This is a MIXTURE; no registration information contained in this document. Holts are classed as Downstream User.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Car maintenance product. Primer.

1.3. Details of the supplier of the safety data sheet

Supplier Holt Lloyd International Ltd
Barton Dock Road
Stretford
Manchester
M32 0YQ - England, UK
+44 (0) 161 866 4800
FAX +44 (0) 161 866 4854
www.holtsauto.com

Contact person Contact email address: info@holtsauto.com

1.4. Emergency telephone number

Emergency telephone UK - 00 44 (0) 161 866 4800 Office hrs = 0900 - 1700 hrs

National emergency telephone number National Poisons Information Service
City Hospital, Birmingham B187QH, United Kingdom
Telephone: +44 121 507 4123
Email: allistervale@npis.org, sallybradberry@npis.org

www.npis.org

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (SI 2019 No. 720)

Physical hazards Aerosol 1 - H222, H229

Health hazards Eye Irrit. 2 - H319 Skin Sens. 1 - H317 STOT SE 3 - H336

Environmental hazards Aquatic Chronic 3 - H412

2.2. Label elements

Simoniz Underguard

Hazard pictograms



Signal word

Danger

Hazard statements

H222 Extremely flammable aerosol.
 H229 Pressurised container: may burst if heated.
 H319 Causes serious eye irritation.
 H317 May cause an allergic skin reaction.
 H336 May cause drowsiness or dizziness.
 H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P102 Keep out of reach of children.
 P101 If medical advice is needed, have product container or label at hand.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P273 Avoid release to the environment.
 P261 Avoid breathing spray.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
 P302+P352 IF ON SKIN: Wash with plenty of water.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
 P501 Dispose of contents/ container in accordance with local regulations.

UFI

UFI: JCA6-E05X-600Q-74XH

Contains

n-BUTYL ACETATE, ACETONE, ETHYL ACETATE, NAPHTHA (PETROLEUM),
 HYDROTREATED LIGHT, Hydrocarbons, C9, Aromatics, ROSIN

Supplementary precautionary statements

P264 Wash contaminated skin thoroughly after handling.
 P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.
 P337+P313 If eye irritation persists: Get medical advice/ attention.

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

BUTANE		10-30%
CAS number: 106-97-8	EC number: 203-448-7	
Classification		
Flam. Gas 1A - H220		
Press. Gas		

Simoniz Underguard

n-BUTYL ACETATE		10-30%
CAS number: 123-86-4	EC number: 204-658-1	
Classification Flam. Liq. 3 - H226 STOT SE 3 - H336		
ACETONE		5-10%
CAS number: 67-64-1	EC number: 200-662-2	
Classification Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336		
ISOBUTANE		5-10%
CAS number: 75-28-5	EC number: 200-857-2	
Classification Flam. Gas 1A - H220 Press. Gas		
NAPHTHA (PETROLEUM), HYDROTREATED LIGHT		5-10%
CAS number: 64742-49-0	EC number: 265-151-9	
Classification Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411		
ETHYL ACETATE		5-10%
CAS number: 141-78-6	EC number: 205-500-4	
Classification Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336		
Hydrocarbons, C9, Aromatics		1-5%
CAS number: 128601-23-0	EC number: 918-668-5	
Classification Flam. Liq. 3 - H226 STOT SE 3 - H335, H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411		

Simoniz Underguard

ROSIN		1-5%
CAS number: 8050-09-7	EC number: 232-475-7	
Classification Skin Sens. 1 - H317		
XYLENE		1-5%
CAS number: 1330-20-7	EC number: 215-535-7	
Classification Flam. Liq. 3 - H226 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315		

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Keep affected person away from heat, sparks and flames. Move affected person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep affected person warm and at rest. Get medical attention immediately.
Ingestion	Not relevant.
Skin contact	Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.
Eye contact	If liquid has entered the eyes, proceed as follows. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure. Get medical attention promptly if symptoms occur after washing.
Inhalation	Vapours may cause headache, fatigue, dizziness and nausea.
Ingestion	No harmful effects expected from quantities likely to be ingested by accident.
Skin contact	Prolonged skin contact may cause redness and irritation.
Eye contact	Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
-----------------------------	------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with the following media: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.
-------------------------------------	---

5.2. Special hazards arising from the substance or mixture

Specific hazards	Risk of explosion if heated. Containers can burst violently or explode when heated, due to excessive pressure build-up.
-------------------------	---

Simoniz Underguard

5.3. Advice for firefighters

Protective actions during firefighting Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions For personal protection, see Section 8.

6.2. Environmental precautions

Environmental precautions Not considered to be a significant hazard due to the small quantities used.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Wear protective clothing as described in Section 8 of this safety data sheet.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health hazards. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

BUTANE

Long-term exposure limit (8-hour TWA): WEL 600 ppm 1450 mg/m³

Short-term exposure limit (15-minute): WEL 750 ppm 1810 mg/m³

n-BUTYL ACETATE

Long-term exposure limit (8-hour TWA): WEL 150 ppm 724 mg/m³

Short-term exposure limit (15-minute): WEL 200 ppm 966 mg/m³

ACETONE

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m³

Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m³

ISOBUTANE

Long-term exposure limit (8-hour TWA): OES 800 ppm

Short-term exposure limit (15-minute): OES 800 ppm

ETHYL ACETATE

Simoniz Underguard

Long-term exposure limit (8-hour TWA): WEL 200 ppm

Short-term exposure limit (15-minute): WEL 400 ppm

XYLENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm 220 mg/m³

Short-term exposure limit (15-minute): WEL 100 ppm 441 mg/m³

Sk

WEL = Workplace Exposure Limit.

Sk = Can be absorbed through the skin.

Ingredient comments

WEL = Workplace Exposure Limits

n-BUTYL ACETATE (CAS: 123-86-4)

DNEL

Workers - Inhalation; Long term systemic effects: 300 mg/m³
 Workers - Inhalation; Short term systemic effects: 600 mg/m³
 Workers - Inhalation; Long term local effects: 300 mg/m³
 Workers - Inhalation; Short term local effects: 600 mg/m³
 Workers - Dermal; Long term systemic effects: 11 mg/kg bw/day
 Workers - Dermal; Short term systemic effects: 11 mg/kg bw/day
 General population - Inhalation; Long term systemic effects: 35.7 mg/m³
 General population - Inhalation; Short term systemic effects: 300 mg/m³
 General population - Inhalation; Long term local effects: 35.7 mg/m³
 General population - Inhalation; Short term local effects: 300 mg/m³
 General population - Dermal; Long term systemic effects: 6 mg/kg bw/day
 General population - Dermal; Short term systemic effects: 6 mg/kg bw/day
 General population - Oral; Long term systemic effects: 2 mg/kg bw/day
 General population - Oral; Short term systemic effects: 6 mg/kg bw/day

PNEC

Fresh water; 0.18 mg/l
 marine water; 0.018 mg/l
 STP; 35.6 mg/l
 Sediment (Freshwater); 0.981 mg/kg sediment dry weight
 Sediment (Marinewater); 0.098 mg/kg sediment dry weight
 Soil; 0.09 mg/kg soil dry weight

ACETONE (CAS: 67-64-1)

DNEL

Consumer - Oral; Long term systemic effects: 62 mg/kg/day
 Workers - Dermal; Long term systemic effects: 186 mg/kg/day
 Consumer - Dermal; Long term systemic effects: 62 mg/kg/day
 Workers - Inhalation; Short term local effects: 2420 mg/m³
 Workers - Inhalation; Long term systemic effects: 1210 mg/m³
 Consumer - Inhalation; Long term systemic effects: 200 mg/m³

PNEC

Fresh water; 10.6 mg/l
 marine water; 1.06 mg/l
 Intermittent release; 21 mg/l
 Sediment (Freshwater); 30.4 mg/kg
 Sediment (Marinewater); 3.04 mg/kg
 Soil; 29.5 mg/kg
 STP; 100 mg/l

ETHYL ACETATE (CAS: 141-78-6)

Simoniz Underguard

DNEL	Workers - Inhalation; Long term systemic effects: 734 mg/m ³
	Workers - Inhalation; Short term systemic effects: 1468 mg/m ³
	Workers - Inhalation; Long term local effects: 734 mg/m ³
	Workers - Inhalation; Short term local effects: 1468 mg/m ³
	Workers - Dermal; Long term systemic effects: 63 mg/kg bw/day
	General population - Inhalation; Long term systemic effects: 367 mg/m ³
	General population - Inhalation; Short term systemic effects: 734 mg/m ³
	General population - Inhalation; Long term local effects: 367 mg/m ³
	General population - Inhalation; Short term local effects: 734 mg/m ³
	General population - Dermal; Long term systemic effects: 37 mg/kg bw/day
	General population - Oral; Long term systemic effects: 4.5 mg/kg bw/day
PNEC	Fresh water; 0.24 mg/l
	marine water; 0.024 mg/l
	STP; 650 mg/l
	Sediment (Freshwater); 1.15 mg/kg sediment dry weight
	Sediment (Marinewater); 0.115 mg/kg sediment dry weight
	Soil; 0.148 mg/kg soil dry weight

NAPHTHA (PETROLEUM), HYDROTREATED LIGHT (CAS: 64742-49-0)

DNEL	Workers - Inhalation; Short term systemic effects: 1286.4 mg/m ³
	Workers - Inhalation; Long term local effects: 837.5 mg/m ³
	General population - Inhalation; Short term systemic effects: 1152 mg/m ³
	General population - Inhalation; Long term local effects: 178.6 mg/m ³
	General population - Inhalation; Short term local effects: 640 mg/m ³

Hydrocarbons, C9, Aromatics (CAS: 128601-23-0)

DNEL	Workers - Inhalation; Long term systemic effects: 150 mg/m ³
	Workers - Dermal; Long term systemic effects: 25 mg/kg bw/day
	General population - Inhalation; Long term systemic effects: 32 mg/m ³
	General population - Dermal; Long term systemic effects: 56 mg/kg bw/day
	General population - Oral; Long term systemic effects: 56 mg/kg bw/day

ROSIN (CAS: 8050-09-7)

DNEL	Workers - Inhalation; Long term local effects: 10 mg/m ³
	Workers - Dermal; Long term systemic effects: 2.131 mg/kg bw/day
	General population - Dermal; Long term systemic effects: 1.065 mg/kg bw/day
	General population - Oral; Long term systemic effects: 1.065 mg/kg bw/day

PNEC	Fresh water; 0.002 mg/l
	marine water; 0.0002 mg/l
	STP; 1000 mg/l
	Sediment (Freshwater); 0.007 mg/kg sediment dry weight
	Sediment (Marinewater); 0.001 mg/kg sediment dry weight

XYLENE (CAS: 1330-20-7)

Simoniz Underguard

DNEL

Consumer - Dermal; Long term systemic effects: 108 mg/kg/day
 Workers - Dermal; Long term systemic effects: 180 mg/kg/day
 Consumer - Inhalation; Short term local effects: 174 mg/m³
 Consumer - Inhalation; Short term systemic effects: 174 mg/m³
 Workers - Inhalation; Short term systemic effects: 289 mg/m³
 Workers - Inhalation; Short term local effects: 289 mg/m³
 Consumer - Inhalation; Long term systemic effects: 14.8 mg/m³
 Workers - Inhalation; Long term systemic effects: 77 mg/m³

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles or face shield.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. It is recommended that gloves are made of the following material: Rubber (natural, latex). To protect hands from chemicals, wear gloves that are proven to be impervious to the chemical and resist degradation.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Hygiene measures

Use engineering controls to reduce air contamination to permissible exposure level. Do not smoke in work area. Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Do not eat, drink or smoke when using this product.

Respiratory protection

No specific recommendations. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Aerosol.
Colour	Black.
Odour	Organic solvents.
pH	Not relevant.
Flash point	<0°C Closed cup.
Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 4.8 Upper flammable/explosive limit: 9.5
Relative density	0.860 - 0.900 @ 20°C
Solubility(ies)	Soluble in water.

9.2. Other information

SECTION 10: Stability and reactivity

Simoniz Underguard

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Not applicable.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid contact with the following materials: Strong oxidising agents. Strong alkalis. Strong mineral acids.

10.5. Incompatible materials

Materials to avoid No specific material or group of materials is likely to react with the product to produce a hazardous situation.

10.6. Hazardous decomposition products

Hazardous decomposition products Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO₂).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects No information available.

Acute toxicity - oral

Notes (oral LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

ATE dermal (mg/kg) 70,964.64

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Based on available data the classification criteria are not met.

ATE inhalation (vapours mg/l) 390.31

Skin corrosion/irritation

Skin corrosion/irritation Based on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye damage/irritation Causes serious eye irritation.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met.

Genotoxicity - in vivo Based on available data the classification criteria are not met.

Carcinogenicity

Simoniz Underguard

Carcinogenicity Based on available data the classification criteria are not met.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure Central and/or peripheral nervous system damage.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Based on available data the classification criteria are not met.

Inhalation Extensive use of the product in areas with inadequate ventilation may result in the accumulation of hazardous vapour concentrations. May cause eye and respiratory system irritation. Symptoms following overexposure may include the following: Headache. Vapours may cause headache, fatigue, dizziness and nausea.

Ingestion No harmful effects expected from quantities likely to be ingested by accident.

Skin contact Prolonged and frequent contact may cause redness and irritation.

Eye contact Vapour or spray in the eyes may cause irritation and smarting.

Toxicological information on ingredients.

XYLENE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 3,523.0

Species Rat

ATE oral (mg/kg) 3,523.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 2,000.0

Species Rabbit

ATE dermal (mg/kg) 2,000.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 29,000.0

Species Rat

Species Human

ATE inhalation (vapours mg/l) 11.0

Skin corrosion/irritation

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/irritation

Serious eye damage/irritation Causes serious eye irritation.

Simoniz Underguard

Carcinogenicity

IARC carcinogenicity IARC Group 3 Not classifiable as to its carcinogenicity to humans.

Aspiration hazard

Aspiration hazard May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

Ecotoxicity The product is not expected to be hazardous to the environment. The product components are not classified as environmentally hazardous. However, large or frequent spills may have hazardous effects on the environment.

12.1. Toxicity

Acute aquatic toxicity

Acute toxicity - fish Not available.

Acute toxicity - aquatic invertebrates Not available.

Acute toxicity - aquatic plants Not available.

Acute toxicity - microorganisms Not available.

Acute toxicity - terrestrial Not available.

Chronic aquatic toxicity

Chronic toxicity - fish early life stage Not available.

Short term toxicity - embryo and sac fry stages Not available.

Chronic toxicity - aquatic invertebrates Not available.

Ecological information on ingredients.

XYLENE

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 13.5 hours: 96 mg/l, Fish

Acute toxicity - aquatic invertebrates EC₅₀, 7.4 hours: 48 mg/l, Daphnia magna

Acute toxicity - aquatic plants IC₅₀, 72 hours: 1-10 mg/l, Algae

12.2. Persistence and degradability

Persistence and degradability The product is expected to be biodegradable.

Ecological information on ingredients.

XYLENE

Biodegradation The substance is readily biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential The product is not bioaccumulating.

Simoniz Underguard

12.4. Mobility in soil

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces. The product is soluble in water. The product hardens to a solid, immobile substance.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Empty containers must not be punctured or incinerated because of the risk of an explosion. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950
UN No. (ADN)	1950

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	AEROSOLS
Proper shipping name (IMDG)	AEROSOLS
Proper shipping name (ICAO)	AEROSOLS
Proper shipping name (ADN)	AEROSOLS

14.3. Transport hazard class(es)

ADR/RID class	2.1
ADR/RID classification code	5F
ADR/RID label	2.1
IMDG class	2.1
ICAO class/division	2.1
ADN class	2.1

Transport labels



14.4. Packing group

ADR/RID packing group None

Simoniz Underguard

IMDG packing group None

ICAO packing group None

ADN packing group None

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

EmS F-D, S-U

ADR transport category 2

Tunnel restriction code (D)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78
and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).

Authorisations (SI 2020 No. 1577 Annex XIV) No specific authorisations are known for this product.

Restrictions (SI 2020 No. 1577 Annex XVII) No specific restrictions on use are known for this product.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
 ATE: Acute Toxicity Estimate.
 BOD: Biochemical Oxygen Demand.
 CAS: Chemical Abstracts Service.
 DNEL: Derived No Effect Level.
 EC₅₀: 50% of maximal Effective Concentration.
 GHS: Globally Harmonized System.
 IATA: International Air Transport Association.
 ICAO: Technical Instructions for the Safe Transport of Dangerous Goods by Air.
 LC50: Lethal Concentration to 50 % of a test population.
 LD50: Lethal Dose to 50% of a test population (Median Lethal Dose).
 NOAEL: No Observed Adverse Effect Level.
 NOEC: No Observed Effect Concentration.
 PBT: Persistent, Bioaccumulative and Toxic substance.
 PNEC: Predicted No Effect Concentration.
 REACH: The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020 No. 1577.
 SVHC: Substances of Very High Concern.
 vPvB: Very Persistent and Very Bioaccumulative.

Simoniz Underguard

Revision date 30/03/2020

Revision 3

Supersedes date 17/01/2017

SDS number 15055

Hazard statements in full

- H220 Extremely flammable gas.
- H222 Extremely flammable aerosol.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H229 Pressurised container: may burst if heated.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.